

IN THE CLAIMS

Please amend claims 1 - 7, 10 - 14, 17 - 18, 20, 36 - 42, 46 - 49, 52 - 53, 55, 57 - 66 by replacing all previous claim sets with the claim set which follows

Sub 017
B3
1. (CURRENTLY AMENDED) A ~~telecommunications network wherein a user~~ equipment unit (UE) which, while communicating with a telecommunications network using one of a cell or a current active set of base stations on a first frequency, maintains a virtual active set of plural base stations on a second frequency and performs a measurements respecting a signals on the second frequency for the respective plural base stations of the virtual active set, whereby the user equipment unit (UE) can switch to the virtual active set of plural base stations upon performance of an inter-frequency handover ~~when the measurement made at the user equipment unit (UE) so warrants.~~

2. (CURRENTLY AMENDED) The apparatus network of claim 1, wherein the measurements made at the user equipment unit (UE) ~~is~~ are triggered either periodically, immediately, or in response to a predetermined event.

3. (CURRENTLY AMENDED) The apparatus network of claim 1, wherein in response to a measurement trigger criteria, the user equipment unit (UE) performs and reports inter-frequency measurements for the second frequency.

4. (CURRENTLY AMENDED) The apparatus network of claim 3, wherein the measurement trigger criteria which causes the user equipment unit (UE) to perform and report inter-frequency measurements for the second frequency is the same criteria which is employed to cause the user equipment unit (UE) to perform and report intra-frequency measurements for the first frequency..

5. (CURRENTLY AMENDED) The ~~apparatus network~~ of claim 3, wherein the measurement trigger criteria is one of being periodic ~~periodically~~, immediate, or in response to a predetermined event.

Sub 017
6. (CURRENTLY AMENDED) ~~The network of claim 1,~~ A telecommunications network wherein a user equipment unit (UE), while using one of a cell or a current active set of base stations on a first frequency, maintains a virtual active set of plural base stations on a second frequency and performs measurements respecting signals on the second frequency for the respective plural base stations of the virtual active set;

B3
wherein when ~~the measurement made at the user equipment unit (UE) so warrants,~~ the network issues an inter-frequency handover command to the user equipment unit ~~(UE) so that,~~ the user equipment unit (UE) switches to the virtual active set of base stations.

7. (CURRENTLY AMENDED) The network of claim ~~6~~1, wherein the network provides information regarding the virtual active set of base stations on the second frequency in a measurement control message.

8. (ORIGINAL) The network of claim 7, wherein the measurement control message is included in a DCCH control channel.

9. (ORIGINAL) The network of claim 7, wherein the measurement control message further includes one of a measurement parameter to be measured and a predetermined measurement event which triggers a measurement.

10. (CURRENTLY AMENDED) The network of claim ~~6~~1, wherein the network provides at least one member of the virtual active set of base stations on the second frequency in a virtual active set update procedure.

11. (CURRENTLY AMENDED) The apparatus network of claim 1, wherein the ~~network sends the~~ user equipment unit (UE) receives from the network an authorization message that allows the user equipment unit (UE) to autonomously update the virtual active set of base stations ~~when the measurement made at the user equipment unit (UE)~~ ~~so warrants.~~

63 12. (CURRENTLY AMENDED) The apparatus network of claim 11, wherein the authorization message specifies one of an event or a parameter that can trigger the update of the virtual active set of base stations without the user equipment unit (UE) first having to send a measurement report to the network.

13. (CURRENTLY AMENDED) The network of claim 61, wherein the virtual active set of base stations on the second frequency is maintained by a second operator which differs from a first operator which maintains the current active set of base stations on the first frequency.

14. (CURRENTLY AMENDED) The network of claim 61, wherein the virtual active set of base stations on the second frequency comprises a second network system which differs from a first network system provided on the first frequency.

15. (ORIGINAL) The network of claim 14, wherein the second network system is universal mobile telecommunications (UMTS) and the first network system is a Global System for Mobile (GSM) system.

16. (ORIGINAL) The network of claim 14, wherein the second network system is a system having soft intra-frequency handover and the first network system is universal mobile telecommunications (UMTS).

17. (CURRENTLY AMENDED) The network of claim ~~64~~, wherein the network utilizes a frequency quality estimate to determine when ~~the measurement made at the user equipment unit (UE) warrants the~~ to switch to the virtual active set of base stations.

18. (CURRENTLY AMENDED) The network of claim 17, wherein the frequency quality estimate is provided by the equation.

$$Q_{carrier\ j} = 10 \cdot \text{Log} M_{carrier\ j} = 10 \cdot \text{Log} \left(W_j \cdot \left(\sum_{i=1}^{N_A} M_{i\ j} \right) + (1 - W_j) \cdot M_{Best\ j} \right)$$

wherein:

$Q_{frequency\ j}$ is the estimated quality of the active set on frequency j ;

$M_{frequency\ j}$ is the estimated quality of the active set on frequency j ;

M_i is a measurement result of cell i in the active set;

N_A is the number of cells in the active set;

M_{Best} is the measurement result of the strongest cell in the active set;

W is a parameter with the value range 1-0 sent from ~~UTRAN~~ the network to the user equipment unit(UE);

wherein when $W=0$ only the measurement results from the best cell on frequency j is used; and

when $W=1$ only the sum of the measurement results from the cells in the active set is used.

19. (ORIGINAL) The network of claim 17, wherein the frequency quality estimate is based on two factors: (1) a carrier Radio Signal Strength Indication (RSSI); and (2) whether the Base Transceiver Station Identity Code/Base Station Identifier Code (BSIC) has been confirmed or not.

20. (CURRENTLY AMENDED) The network of claim 17, wherein the network compares the frequency quality estimate to at least one threshold to determine when ~~the measurement made at the user equipment unit (UE) warrants the~~ to switch to the virtual active set of base stations.

21. (ORIGINAL) The network of claim 20, wherein the at least one threshold is chosen to provide hysteresis protection.

b3
22. {CANCELLED}

23. {CANCELLED} .

24. {CANCELLED}

25. {CANCELLED}

26. {CANCELLED}

27. {CANCELLED}

28. {CANCELLED}

29. {CANCELLED}

30. {CANCELLED}

31. {CANCELLED}

32. {CANCELLED}

33. {CANCELLED}

34. {CANCELLED}

35. {CANCELLED}

B3 sub C17

36. (CURRENTLY AMENDED) A method of operating a ~~telecommunications network~~ user equipment unit (UE) which communications with a telecommunications system, the method comprising: the ~~a user equipment unit (UE);~~
while using one of a cell or a current active set of base stations on a first frequency; ~~maintaining~~ a virtual active set of plural base stations on a second frequency;
performing ~~a measurements~~ respecting a signals on the second frequency for the respective plural base stations of the virtual active set;
~~the user equipment unit (UE) switching to the virtual active set of plural~~ base stations upon performance of an inter-frequency handover when the measurement made at the user equipment unit (UE) so warrants.

37. (PREVIOUSLY AMENDED) The method of claim 36, further comprising triggering the measurements made at the user equipment unit ~~(UE)~~ either periodically, immediately, or in response to a predetermined event.

38. (CURRENTLY AMENDED) The method of claim 36, further comprising the user equipment unit ~~(UE)~~ performing and reporting inter-frequency measurements for the second frequency in response to a measurement trigger criteria.

39. (CURRENTLY AMENDED) The method of claim 38, wherein the measurement trigger criteria which causes the user equipment unit (UE) to perform and report inter-frequency measurements for the second frequency is the same criteria which is employed to cause the user equipment unit (UE) to perform and report intra-frequency measurements for the first frequency.

40. (CURRENTLY AMENDED) The method of claim 38, wherein the measurement trigger criteria is one of being periodic ~~periodically~~, immediate, or in response to a predetermined event.

B3
Sub 017

41. (CURRENTLY AMENDED) ~~The method of claim 36, further comprising,~~
A method of operating a telecommunications network which communicates with a user equipment unit (UE), the user equipment unit (UE), while using one of a cell or a current active set of base stations on a first frequency, maintaining a virtual active set of plural base stations on a second frequency; and performing measurements respecting signals on the second frequency for the respective plural base stations of the virtual active set; the method comprising:

~~when the measurement made at the user equipment unit (UE) so warrants, the network issuing performing an inter-frequency handover command to the user equipment unit (UE) so that the user equipment unit (UE) switches to the virtual active set of plural base stations.~~

42. (CURRENTLY AMENDED) The method of claim 41 ~~36~~, further comprising the network providing information regarding the virtual active set of base stations on the second frequency in a measurement control message.

43. (ORIGINAL) The method of claim 42, further comprising including the measurement control message in a DCCH control channel.

44. (ORIGINAL) The method of claim 42, further comprising including in the measurement control message further one of a measurement parameter to be measured and a predetermined measurement event which triggers a measurement.

45. (ORIGINAL) The method of claim 36, further comprising the network providing at least one member of the virtual active set of base stations on the second frequency in a virtual active set update procedure.

B3
46. (CURRENTLY AMENDED) The method of claim 36, further comprising the user equipment unit ~~(UE)~~ receiving from the network ~~sending the user equipment unit (UE)~~ an authorization message that allows the user equipment unit (UE) to update autonomously the virtual active set of base stations ~~when the measurement made at the user equipment unit (UE) so warrants.~~

47. (CURRENTLY AMENDED) The method of claim 46, wherein further ~~comprising specifying in the authorization message~~ includes one of an event or a parameter that can trigger the update of the virtual active set of base stations without the user equipment unit (UE) first having to send a measurement report to the network.

48. (CURRENTLY AMENDED) The method of claim ~~41~~ 36, further comprising: maintaining the virtual active set of base stations on the second frequency by a second operator which differs from a first operator which maintains the current active set of base stations on the first frequency.

49. (CURRENTLY AMENDED) The method of claim ~~41~~ 36, wherein the virtual active set of base stations on the second frequency comprises a second network system which differs from a first network system provided on the first frequency.

50. (ORIGINAL) The method of claim 49, wherein the second network system is universal mobile telecommunications (UMTS) and the first network system is a system having soft intra-frequency handover.

51. (ORIGINAL) The method of claim 49, wherein the second network system is a Global System for Mobile (GSM) system and the first network system is universal mobile telecommunications (UMTS).

63
52. (CURRENTLY AMENDED) The method of claim ~~41~~ 36, further comprising using a frequency quality estimate to determine when ~~the measurement made at the user equipment unit (UE) warrants the~~ to switch to the virtual active set of base stations.

53. (CURRENTLY AMENDED) The method of claim 52, wherein the frequency quality estimate is provided by the equation.

$$Q_{carrier\ j} = 10 \cdot \text{Log} M_{carrier\ j} = 10 \cdot \text{Log} \left(W_j \cdot \left(\sum_{i=1}^{N_A} M_{i\ j} \right) + (1 - W_j) \cdot M_{Best\ j} \right)$$

wherein:

$Q_{frequency\ j}$ is the estimated quality of the active set on frequency j;

$M_{frequency\ j}$ is the estimated quality of the active set on frequency j;

M_i is a measurement result of cell i in the active set;

N_A is the number of cells in the active set;

M_{Best} is the measurement result of the strongest cell in the active set;

W is a parameter with the value range 1-0 sent from ~~UTRAN~~ the network to the user equipment unit (UE);

wherein when $W=0$ only the measurement results from the best cell on frequency j is used; and

when $W=1$ only the sum of the measurement results from the cells in the active set is used.

54. (ORIGINAL) The method of claim 52, wherein the frequency quality estimate is based on two factors: (1) a carrier/Radio Signal Strength Indication (RSSI); and (2) whether the Base Transceiver Station Identity Code/Base Station Identifier Code (BSIC) has been confirmed or not.

55. (CURRENTLY AMENDED) The method of claim 52, wherein the network compares the frequency quality estimate to at least one threshold to determine when ~~the measurement made at the user equipment unit (UE) warrants the~~ to switch to the virtual active set of base stations.

56. (ORIGINAL) The method of claim 55, wherein the at least one threshold is chosen to provide hysteresis protection.

57. (CURRENTLY AMENDED) The apparatus ~~network~~ of claim 1, wherein the signal for which the user equipment unit (~~UE~~) performs the measurement is a physical control channel on the second frequency.

58. (CURRENTLY AMENDED) The apparatus ~~network~~ of claim 1, wherein the cells which belong to the virtual active set on the second frequency are cells which would be considered in the active set on the second frequency if the user equipment unit (~~UE~~) were to use the second frequency for active traffic.

59. (CURRENTLY AMENDED) The network of claim 22, wherein the signal for which the user equipment unit (~~UE~~) performs the measurement is a physical control channel on the second frequency.

60. (CURRENTLY AMENDED) The network of claim 22, wherein the cells which belong to the virtual active set on the second frequency are cells which would be considered in the active set on the second frequency if the user equipment unit (UE) were to use the second frequency for active traffic.

61. (CURRENTLY AMENDED) The network of claim 28, wherein the signal for which the user equipment unit (UE) performs the measurement is a physical control channel on the second frequency.

b3 62. (CURRENTLY AMENDED) The network of claim 28, wherein the cells which belong to the virtual active set on the second frequency are cells which would be considered in the active set on the second frequency if the user equipment unit (UE) were to use the second frequency for active traffic.

63. (CURRENTLY AMENDED) The method of claim 36, wherein the signal for which the user equipment unit (UE) performs the measurement is a physical control channel on the second frequency.

64. (CURRENTLY AMENDED) The method of claim 36, wherein the cells which belong to the virtual active set on the second frequency are cells which would be considered in the active set on the second frequency if the user equipment unit (UE) were to use the second frequency for active traffic.

65. (CURRENTLY AMENDED) A telecommunications network wherein a user equipment unit (UE), while using one of a cell of a current active set of base stations on a first frequency, maintains a virtual active set of base stations on a second frequency, whereby the user equipment unit (UE) can switch to the virtual active set of base stations

~~when frequency measurements made at the user equipment unit (UE) so warrants, and wherein the network sends the user equipment unit (UE) an authorization message that allows the user equipment unit (UE) to autonomously update the virtual active set of base stations when the frequency measurements made at the user equipment unit (UE) so warrants.~~

63 66. (CURRENTLY AMENDED) The network of claim 65, wherein the authorization message specifies one of an event or a parameter that can trigger the update of the virtual active set of base stations without the user equipment unit (UE) first having to send a measurement report to the network.

67. (NEW) A user equipment unit which, while communicating with a telecommunications network using one of a cell or a current active set of base stations which operate on a first frequency, performs measurements respecting signals of a second frequency from each of plural base stations which operate on the second frequency, and maintains as a virtual active set plural base stations which operate on the second frequency and which satisfy network-specified criteria, so that when an inter-frequency handover is required the virtual active set can essentially immediately be utilized as the active set for the user equipment whereby the user equipment unit can be in radio communication with each of the plural base stations in the virtual active set.

68. (NEW) The apparatus of claim 67, wherein the measurements made at the user equipment unit is triggered either periodically, immediately, or in response to a predetermined event.

69. (NEW) The apparatus of claim 67, wherein in response to a measurement trigger criteria, the user equipment unit performs and reports inter-frequency measurements for the second frequency.

70. (NEW) The apparatus of claim 69, wherein the measurement trigger criteria which causes the user equipment unit to perform and report inter-frequency measurements for the second frequency is the same criteria which is employed to cause the user equipment unit to perform and report intra-frequency measurements for the first frequency.

71. (NEW) The apparatus of claim 67, wherein the measurement trigger criteria is one of being periodic, immediate, or in response to a predetermined event.

63 72. (NEW) The apparatus of claim 67, wherein when the network issues an inter-frequency handover command to the user equipment unit, the user equipment unit switches to the virtual active set of base stations.

73. (NEW) The apparatus of claim 67, wherein the network provides information regarding the virtual active set of base stations on the second frequency in a measurement control message.

74. (NEW) The apparatus of claim 73, wherein the measurement control message is included in a DCCH control channel.

75. (NEW) The apparatus of claim 73, wherein the measurement control message further includes one of a measurement parameter to be measured and a predetermined measurement event which triggers a measurement.

76. (NEW) The apparatus of claim 67, wherein the network provides at least one member of the virtual active set of base stations on the second frequency in a virtual active set update procedure.

77. (NEW) The apparatus of claim 67, wherein the user equipment unit receives from the network an authorization message that allows the user equipment unit to autonomously update the virtual active set of base stations.

78. (NEW) The apparatus of claim 77, wherein the authorization message specifies one of an event or a parameter that can trigger the update of the virtual active set of base stations without the user equipment unit first having to send a measurement report to the network.

B3 79. (NEW) The network of claim 67, wherein the virtual active set of base stations on the second frequency is maintained by a second operator which differs from a first operator which maintains the current active set of base stations on the first frequency.

80. (NEW) The apparatus of claim 67, wherein the virtual active set of base stations on the second frequency comprises a second network system which differs from a first network system provided on the first frequency.

81 (NEW) The apparatus of claim 80, wherein the second network system is universal mobile telecommunications (UMTS) and the first network system is a Global System for Mobile (GSM) system.

82. (NEW) The apparatus of claim 80, wherein the second network system is a system having soft intra-frequency handover and the first network system is universal mobile telecommunications (UMTS).

83. (NEW) The apparatus of claim 67, wherein the network utilizes a frequency quality estimate to determine when ~~the measurement made at the user equipment unit warrants the~~ to switch to the virtual active set of base stations.

84. (NEW) The apparatus of claim 83, wherein the frequency quality estimate $Q_{\text{carrier } j}$ of the active set on frequency j is a function of the following parameters:

$$W_j, \sum_{i=1}^{N_A} M_{ij}, M_{\text{Best } j}$$

wherein:

M_i is a measurement result of cell i in the active set;

N_A is the number of cells in the active set;

M_{Best} is the measurement result of the strongest cell in the active set;

W is a parameter sent from the network to the user equipment unit.

85. (NEW) The apparatus of claim 83, wherein the frequency quality estimate is based on two factors: (1) a carrier Radio Signal Strength Indication (RSSI); and (2) whether the Base Transceiver Station Identity Code/Base Station Identifier Code (BSIC) has been confirmed or not.

86. (NEW) The apparatus of claim 83, wherein the network compares the frequency quality estimate to at least one threshold to determine when to switch to the virtual active set of base stations.

87. (NEW) The apparatus of claim 86, wherein the at least one threshold is chosen to provide hysteresis protection.

88. (NEW) A user equipment unit which, while communicating with a telecommunications network using one of a cell or a current active set of base stations

which operate on a first frequency, performs measurements respecting (1) signals of a second frequency from each of plural base stations which operate on the second frequency and (2) signals of a third frequency from each of plural base stations which operate on the third frequency; and maintains (1) as a first virtual active set plural base stations which operate on the second frequency and which satisfy network-specified criteria and (2) as a second virtual active set plural base stations which operate on the third frequency and which satisfy the network-specified criteria; so that when an inter-frequency handover is required one of the first virtual active set and the second active set can essentially immediately be utilized as the active set for the user equipment.

63
89. (NEW) The apparatus of claim 88, wherein one of the first virtual active set of base stations on the second frequency and the second virtual active set of base stations on the third frequency is maintained by a second operator which differs from a first operator which maintains the current active set of base stations on the first frequency.

90. (NEW) The apparatus of claim 88, wherein one of the first virtual active set of base stations on the second frequency and the second virtual active set of base stations on the third frequency comprises a second network system which differs from a first network system provided on the first frequency.

91. (NEW) The apparatus of claim 90, wherein the second network system is universal mobile telecommunications (UMTS) and the first network system is a Global System for Mobile (GSM) system.

92. (NEW) The apparatus of claim 17, wherein the frequency quality estimate $Q_{\text{carrier } j}$ of the active set on frequency j is a function of the following parameters:

$$W_j, \sum_{i=1}^{N_{A_j}} M_{ij}, M_{\text{Best } j}$$

wherein:

M_i is a measurement result of cell i in the active set;

N_A is the number of cells in the active set;

M_{Best} is the measurement result of the strongest cell in the active set;

W is a parameter sent from the network to the user equipment unit.

93. (NEW) The method of claim 52, wherein the frequency quality estimate $Q_{carrier j}$ of the active set on frequency j is a function of the following parameters:

63

$$W_j, \sum_{i=1}^{N_{A_j}} M_{ij}, M_{Best j}$$

wherein:

M_i is a measurement result of cell i in the active set;

N_A is the number of cells in the active set;

M_{Best} is the measurement result of the strongest cell in the active set;

W is a parameter sent from the network to the user equipment unit.